



85652 \ 85653 Air Oil Separator kits are designed for vehicles with automatic and standard transmissions. Determine what application applies and follow either “Automatic Transmission” or “Standard Transmission” directions.

Parts List

- (1) TANK BODY
- (2) BILLET CLAMP
- (1) BILLET MOUNT
- (2) STAINLESS STEEL BRACKETS
- (2) 90 DEGREE BARBED FITTINGS
- (1) LENGTH OF 3/8" X 2FT HOSE
- (1) LENGTH OF 3/8" X 5FT HOSE (5 FT LENGTH FOR AUTOMATIC TRANSMISSION VEHICLES, TRIM AS NEEDED FOR STANDARD TRANSMISSION VEHICLES)
- (6) 1/4 X 20 SHCS X 5/8
- (2) HOSE CLAMPS

REVB
31413

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com

85652/85653INST



Vehicles with “Automatic Transmission” Follow steps 1 –14.



Step 1: Remove oil fill cap and engine cover.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time

MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE

GUILFORD, CT 06437

www.moroso.com



Step 2: Re-install oil fill cap.




Step 3: Locate PCV line, runs from drivers side rear valve cover to intake manifold.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com



Step 4: Remove PCV line from valve cover.




Step 5: Remove PCV line from intake.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com




Step 6: Remove PCV line from vehicle.



Step 7: Route 3/8 line from passengers side front of vehicle to drivers side rear valve cover as shown.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.


80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com



For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.
80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com



Step 8: Install hose clamp.




Step 9: Install hose over nipple and tighten hose clamp.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com



Step 10: Coil hose at front of vehicle for future use.




Step 11: Install hose clamp over short length of 3/8 hose.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com



Step 12: Install hose over intake nipple.



Step 13: Route as shown in above illustration.


For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com



Step 14: Reinstall engine cover and oil fill cap.


Vehicles with “Standard Transmissions” Follow Steps 1-8



Step 1: Remove engine cover and locate PCV line that runs from intake to lifter valley.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com



Step 2: Remove PCV line from vehicle.




Step 3: Install hose clamp over 3/8 hose.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com



Step 4: Install hose over lifter valley nipple and tighten hose clamp.



Step 5: Route hose as shown.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com




Step 6: Install hose clamp over 3/8 hose.



Step 7: Install hose over intake nipple and tighten hose clamp.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com




Step 8: Route hoses as shown.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.
80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com



The following steps apply to vehicles with “Automatic” and “Standard Transmissions”




Step 1: Locate radiator and fan shroud mounting bolts on passenger side of vehicle.



Step 2: Remove mounting bolts.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com




Step 3: Install Stainless mounting bracket as shown using mounting bolts previously removed.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com




Step 4: Assemble billet mount to stainless clamp mounting bracket using (1) ¼-20 SHCS.



Step 5: Assemble to stainless steel mounting bracket as shown using (1) ¼-20 SHCS.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com



Step 6: Assemble billet saddle to billet clamp using (2) 1/4x20x5/8 SHCS do not tighten.



Step 7: Assemble billet clamp to stainless mount with relief facing down using (2) 1/4-20 SHCS.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com




Step 8: Install barbed fittings as shown using Teflon tape.



Step 9: Insert Air Oil Separator into billet clamp with barbed fittings facing firewall of vehicle.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com



Step 10: Set Air Oil Separator to 1" as shown.



Step 11: Install 3/8 hoses to Air Oil Separator.


For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.

80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com



Reinstall engine cover and oil fill cap

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.
80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com



Draining of Air Oil Separator is needed; this will depend on driving conditions (i.e.) normal day to day driving check every 1,000 miles until a baseline is established. A good baseline is to drain the Air Oil Separator when it is about HALF full. This will vary with temperatures (cold winters vs. hot summers). For track usage Air Oil Separator will need to be drained after every outing.

For Technical Assistance, call Moroso's Tech Line
(203)-458-0542, 8:30am-5:00pm Eastern Time
MOROSO PERFORMANCE PRODUCTS, INC.
80 CARTER DRIVE
GUILFORD, CT 06437
www.moroso.com